

## **SPECIFICATION DATA\***

Style Name: SP250 Style Number: SP250 **Description: Textured Cut Pile** Fiber Content: 100% PureColor<sup>®</sup> SD BCF Polyester Face Weight ozs/vd<sup>2</sup>: 24 Finished Pile Thickness: 20/32" Gauge: 3/16 Tufts per Inch: 7 Primary Backing: Polypropylene Secondary Backing: Polypropylene Total Weight ozs/vd<sup>2</sup>: 52.48 Density ozs/yds<sup>3</sup>: 1382 Twist information: 4.25 Turns Per Inch (Average) Width: 12'0 Dye Method: Solution Dyed Treatment: Soil & Stain Shield Installation Pattern Repeat: N/A Flammability (Pill Test CPSC FF1-70): Passed FHA DATA UM44D: Type I Class 1 MEA #: 10522 PAR: 3.5 CRI Green Label Plus: Certified GLP9986

\*All specifications are subject to normal manufacturing tolerances.

## **COLORS**

956 Bayside 510 Honey Beige 715 Sandstone 705 Cookie Dough 927 Chrome 530 Doeskin 708 Claystone 701 Sawgrass 390 Gingerbread 742 Fossil 803 Azure 367 Shoreline 783 Ironside 512 Agate 552 Boulder 255 Carbon Crystals

## WARRANTY<sup>+</sup>

Stain	1	Fade	Pet	Soil	Abrasive	Texture	Manufacturing
Resista	nce	Resistance	Stains	Resistance	Wear	Retention	Defects
Lifetin	ne	Lifetime	Lifetime	15 Years	15 Years	N/A	5 Years

\*Exclusions: Non owner occupied residential installations, outdoor installations, residential areas that are prone to being wet (bathrooms, laundry areas, kitchens, etc.), stairs, and areas that receive excessive equipment wear such as home gyms. Other exclusions may apply. Recommended carpet care and routine maintenance must be conducted to maintain warranty coverage.

www.engineeredfloors.com

866.706.9745

info@engineeredfloors.com

6.18.21